

## SPECIFICATIONS

|                                    | Extra-Small Frame  |                    |                    |
|------------------------------------|--|--------------------|--------------------|
| MODEL                              | 6M 95  | 6M 105             | 6M 115             |
| Operator Station                   | Cab  | Cab                | Cab                |
| Engine description                 | PowerTech™ EWL 4.5L (275 cu in.)   |                    |                    |
| Rated engine power                 | 95 HP (70 kW)  | 105 HP (77 kW)     | 115 HP (86 kW)     |
| Maximum engine power               | 105 HP (77 kW)   | 116 HP (86 kW)     | 126 HP (93 kW)     |
| Power boost                        | 10%  |                    |                    |
| Intelligent Power Management (IPM) | Up to 20 HP  |                    |                    |
| Rated PTO power (HP SAE)           | 70 HP (52 kW)  | 79 HP (59 kW)      | 88 HP (66 kW)      |
| PTO torque rise                    | 40%  |                    |                    |
| Engine peak torque @ 1600 rpm      | 328 ft-lb (445 Nm)   | 362 ft-lb (492 Nm) | 396 ft-lb (538 Nm) |
| Transmission                       | <p><b>Standard:</b> John Deere 24-speed PowrQuad Plus 25 mph (40 km/h)</p> <p><b>Optional:</b> John Deere 16-speed PowrQuad Plus 19 mph (30 km/h); John Deere 24-speed AutoQuad Plus 25 mph (40 km/h) &amp; 31 mph (50 km/h); John Deere 24-speed CommandQuad Plus 25 mph (40 km/h) &amp; 31 mph (50 km/h); AutoPower™/IVT™ 25 mph (40 km/h) &amp; 31 mph (50 km/h)</p> <p><b>Creepers available:</b> PowrQuad Plus; AutoQuad Plus</p> |                    |                    |
| Hydraulic pump rated output        | <p><b>Standard:</b> 35-cc pump: 80 L/min 21 gpm</p> <p><b>Optional:</b> 45-cc pump: 114 L/min 30 gpm</p>   |                    |                    |
| Rear hitch (SAE designation)       | <p><b>Standard:</b> Category 2/3N: 6,057 lb (2,750 kg)</p> <p><b>Optional:</b> Category 2/3N: 7,930 lb (3,600 kg)</p>  |                    |                    |
| Front hitch                        | Category 3N lift capacity at hook ends: 7,269 lb (3,300 kg)  |                    |                    |
| Front axle                         | <p><b>Standard:</b> MFWD</p> <p><b>Optional:</b> Two-wheel drive (2WD) Triple-Link Suspension (TLS) MFWD axle (hydro-pneumatic, permanently active, triple link, self-leveling suspension with 3.9-in. [100-mm] suspension range) Triple-Link Suspension MFWD with brakes</p>  |                    |                    |
| Cab suspension                     | <b>Optional:</b> Mechanical Cab Suspension (MCS)   |                    |                    |
| Precision Ag                       | <p><b>Standard:</b> JDLink™</p> <p><b>Optional:</b> G5 Integrated or Universal Display, AutoTrac Ready™</p>  |                    |                    |
| Wheelbase: MFWD                    | 94.5 in. (2,400 mm)  |                    |                    |
| Base machine weight                | 13,779 lb (6,250 kg)   |                    |                    |

\*\*PS (HP ISO) engine speed (EU 2016/1628)